



电机控制器

热泵/暖



• 冗余直流电

• 高功率因数(APFC)软开关

• 具备良好的电磁兼容性

外置
External



输出电流@额定				
MANGO80H-12	12V	6.66A	±5%	10.0A
MANGO80H-15	15V	5.33A	±5%	8.0A
MANGO80H-19	19V	4.21A	±5%	6.3A
MANGO80H-24	24V	3.33A	±5%	5.0A

输出电流				
MDP120-19y	19V	6.3A	190mV	±5%
MDP120-24y	24V	5.0A	240mV	±5%

x1.33"

	输出电流	峰值电流@10S	峰值电流@40mS	总
12V		25.00A	35.0A	±5%
15V		22.00A	30.0A	±5%
19V		18.50A	25.0A	±5%
24V	00A	15.00A	20.0A	±5%
28V	8.57A	12.85A	17.5A	±5%
32V	7.50A	11.25A	15.0A	±5%
36V	6.66A	10.00A	13.3A	±5%
48V	5.00A	7.50A	10.0A	±5%


电源

- 通用AC输入且部分带主动式PFC
- Class I or Class II 结构

- 高效率 > 80% (满载)
- 符合EN55022 / FCC Part 15 Class B Emissions
- 符合EN55011 / FCC Part 15 Class B Emissions
- 3年质保



	5.6A	8.0A
	5.6A	8.0A
	5.6A	8.0A
	5.41A	8.0A
	4.33A	8.0A
	3.61A	8.0A
	2.71A	8.0A



总调整率(含设定点)

产品型号	输出电压	出电流	纹波及噪声(最大值)
------	------	-----	------------



产品型号	V1 输出电压	V1 单输出		V1 +V2 组合输出	
		V1 输出		V1 +V2 组合输出	
		自冷	风冷	自冷	风冷
		13.75A (165W)			
		12.0A (180W)			
		11.1A (200W)			
		10.52A (200W)			
		8.33A (200W)			
		7.14A (200W)			
		5.55A (200W)			

产品型号	输出电压	输出电流	纹波及噪声(最大值)	总调整率(含设定点)
MP300S-12	12V	25.0A	200mV	±2%
MP300S-15	15V	20.0A	200mV	±2%
MP300S-19	19V	15.8A	280mV	±2%
MP300S-24	24V	12.5A	280mV	±2%
MP300S-28	28V	10.8A	280mV	±2%
MP300S-36	36V	8.33A	480mV	±2%
MP300S-48	48V	6.25A	480mV	±2%

MP600U系列

尺寸: 6.5×3.35×1.67"



产品型号	输出电压			
MP600U-12	12V			
MP600U-15	15V			
MP600U-19	19V			
MP600U-24	24V			
MP600U-28	28V			
MP600U-36	36V			
MP600U-48	48V			

此型号带

MP800U系列

产品型号	输出电压		
		33.33A	
		16.67A	

MP400系列

尺寸: 7×3.94×1.58"



MP400-12		30.0A	
MP400-15		26.6A	
		22.2A	
		16.67A	
		14.2A	
		11.1A	
		8.33A	



入电压

9A
6A
7A
1.5A
1.5A
0.1A
12A

150m

