



002851

&

7800

2800



PLC

01/05

MX600
MC8000*
MC6000
MC5000

PLC

06/17

MU400
MU300
MU200
MC700
MC280/MC200E
MC200
MC100
MC160X

16

IO

18/19

MR400
MC5000S

20/24

MDT
MTC/MTCW/MTCV
MTCE
MCAS
MQT

MZ800

25/26

MZ800

MX600

MX600 Series Medium PLC

MX600

256 μs

EtherCAT EtherNET/IP

ProfiNet

99.999%

3C



- 16 /250μs 64 /500us 256 /2ms 20μs
- IO

- 16 16 8
 - 8 4 4 AB
- G-code
- EtherCAT
- 5 4 USB 5 1 HDMI
 - 1 DP
- EtherCAT OPC UA EtherNet/IP Profinet
 - MODBUS RTU MODBUS TCP

		MX610				MX620			
		24V DC -15%~20%							
CPU		N97 2GHz				I3-N305			
		8GB DDR4				16GB DDR4			
		128GB SSD				256GB SSD			
SPI FLASH		64Mbit							
EtherCAT	RS485	3				COM1,COM3,COM4,MODBUS		31	
	RS232	1				COM2		MODBUS-RTU	
	EtherCAT	64+64	LAN1,LAN2			128+128		LAN1,LAN2	
	EtherCAT	256				512			
	ModbusTCP /	3	63			/			
	EtherNet/IP /	1				64		32	
IO	Profinet	1				RT			
	OPC UA	3							
	*8	8 NPN/PNP							
	*8	8 NPN							
	*8	8	200KHZ		AB	4	100KHZ		
	*8	8	4	200KHZ					
	/	4	EtherCAT 64+64			4		EtherCAT	128+128
	/	127				255			
	/CNC	8	3			16		3	
			8						
		IEC 61131-3				LD, ST, SFC, CFC			
		128M Byte							
		Data, Const: 128MB				N	Memory: 5 MB (%M Variable)M		
		Inputs: 128KB %I				Outputs:128KB %Q			
		Persistern: 6MB Retain:1MB Reset Cold							
mm		160* 55* 147							
kg		<1.3Kg							
SD									
EMC		EN61131-2 Zone B							

MC8000

MC8000 Series Medium PLC

MC8000


MEGMEET mOPAX

LD ST SFC CFC FBD IL

PLC

IEC61131-3

EtherCAT Profinet



- 32 ,
- A55
- Modbus/EtherCAT/ EtherNet IP/
- Profinet

- Profinet
 - 8 200K 8 200K
 - + AB
- 1ms/16 EtherCAT 16/
 - 32/64 EtherCAT
- 12mm
 - PUSH in
- 10M 20M 512KB

MC6000

MC6000 Series Medium PLC

MC6000

PLC,

3C

MEGMEET


EtherCAT

PLCopen

Codesys

IEC61131-3

MC6000



- EtherCAT

2ms/16
- ST SFC FBD CFC LD IL IEC61131-3
- 16MB 12MB 256MB

64KB+4KB TF
- MODBUS RTU/TCP Profinet

CANopen EtherCAT
- IO

200KHz IO 8*DI+8*DO)

RS485 CAN,USB TF

		MC6000	MC6010	MC6020
IO		16	1024	
			16M	
			12MB	
			64+4KB	
		I 128KB Q 128K M 4MB		
	()		24.9ns/	
	()		60.9ns/	
	()		50.7ns/	
	()		50.4ns/	
IO		4 AB /8		
		Y0~Y7 4 200KHz		
	Ethernet	2 Modbus TCP /		
	RS485	2 Modbus RTU /		
	OPC UA	4 Client		
		TCP/IP UDP		
		ST LD FBD SFC CFC IL		
EtherCAT		24	12	
		32 ()		
		1ms		
		24 -4ms	12 -4ms	
		24	12	
	/CNC	2	1	
	TF			
	Type-C			

MC6010 profinet	
	Ethernet CAT6
	≤100m()
	100Mbps
	1*RJ45
RT	4ms
IRT	
	1440
	1440

MC6020Ethernet/IP	
	31
	≤100m()
	Ethernet CAT6
	100Mbps
	1*RJ45
	504
	504
CIP	10

MC5000

MC5000 Series Medium PLC


MC5000

PLC

G

3C

EtherCAT



- CPU

EtherCAT : 250μs


64

:2M 100K 8PO

38
- 100K 2.2ms
- C

C 2500dmips
- EtherCAT EtherNet/IP MODBUS RTU

MODBUS TCP



	MC5200E	MC5101EB	MC5100EA	MC5000EA64	MC5000E64	MC5001EB64
IO		16	1024			
		320K				
		2M				
	()	6.4ns				
	()	25ns				
	()	40ns				
	()	50ns				
		2mS/100K				
C		2500dmips				
IO	-	4	6	-	4	
	-	2 AB	1 5V +2 AB	-	2 AB	
IO		16 16	4 4	16 16	4 4	
RS485		8 socket Modbus TCP /				
		2 (Modbus RTU / MCBus)				
		LD SFC FBD C				
EtherCAT		-		64		
	EtherCAT		8			
		256				
		250us		1ms		
		-				
		3 /1				
C	CAD			10000 x2		
	C			C / C		
		C				
	USB SD					

MC5000

	CPU				
	IO				
MC5200E	:16	:16		-	:
MC5100EA	:4 200K	3 1M	:4 6 2M	-	:
MC5101EB	:8 (4 200K)	:8 (4 200K)		-	:
MC5000E8	:16	:16	EtherCAT 8		:
MC5000E16	:16	:16	EtherCAT 16		:
MC5000E32	:16	:16	EtherCAT 32		:
MC5000E64	:16	:16	EtherCAT 64		:
MC5001EB8	:8 (4 200K)	:8 (4 200K)	EtherCAT 8		:
MC5001EB16	:8 (4 200K)	:8 (4 200K)	EtherCAT 16		:
MC5001EB32	:8 (4 200K)	:8 (4 200K)	EtherCAT 32		:
MC5001EB64	:8 (4 200K)	:8 (4 200K)	EtherCAT 64		:
MC5000EA8	:4 200K 3 1M	:4 6 2M	EtherCAT 8		:
MC5000EA16	:4 200K 3 1M	:4 6 2M	EtherCAT 16		:
MC5000EA32	:4 200K 3 1M	:4 6 2M	EtherCAT 32		:
MC5000EA64	:4 200K 3 1M	:4 6 2M	EtherCAT 64		:

MC6000&MC5000

/5000S

IO

MP50AC220	100~240VAC		24V/2A		AC
	IO				
MC5000-3232ETN	32 24VDC	/32			
MC5000-1616ETN	16 24VDC	/16			
MC5000-3200ENN	32 24VDC				
MC5000-0032ETN	32				
MC5000-6400ENN	64 24VDC				
MC5000-0064ETN	64				
MC5000-1600ENN-T	16 24VDC				
MC5000-0016ERN-T	16				
MC5000-0016ETN-T	16				
MC5000-3200ENN-P	32 IO				
MC5000-0032ETN-P	32 IO				
MC5000-1616ETN-PH	16 24VDC	/16 4			
MC5000-1600ENN-P	16 IO				
MC5000-0016ETN-P	16 IO				
MC5000-0016ERN-P	16				
MC5000-0014EPN-P	14				
MC5000-8PO	8 200KHZ	1 4	MC5000		
MC5000-4AD/8AD	4 8				
MC5000-4DA	4				
MC5000-4PT	4				
MC5000-4TC/8TC	4 8				
MC5000-2WT*	2				
MC5000-4DA-P	4				
MC5000-6AD-P	6				
MC5000-8TC-P	8				
	IO				
MC5000S-ET	EtherCAT		EtherCAT		
MC5000S-EIP	EtherNeT/IP		EtherNet/IP		
MC5000S-PN	ProfiNet		ProfiNet		
MCA05-100L	1m				
MCA05-150L	1.5m				
MCA15-40P	40PIN				

MU400

MU400 Series Small PLC

MU400

12mm


mOPAX

16

PLC

IEC-61121-3/PLCopen

LD ST FBD



- 16
- 2

CAN RS485 RS232

- 8 200K
- 8 200K
- + AB

EtherCAT

- 2ms/4
- EtherCAT 8

- 12mm
- PUSH in
-

					x x
MU401	8 DC24V	8	-16 4		105mm x 90mm x 85mm
MU402	8 DC24V	8	-8 4		

			x	x
MR400-4ADI	4		80.7mm x 15.7mm x 107mm	
MR400-4ADV	4			
MR400-4DAI	4			
MR400-4DAV	4			
MR400-0004ERN	4			
MR400-0008EPN	8	PNP		
MR400-0008ETN	8	NPN		
MR400-0016EPN	16	PNP		
MR400-0016ETN	16	NPN		
MR400-0800ENN	8			
MR400-1600ENN	16			
MR400-P2000				

MU300

MU300 Series Small PLC

MU300MEGMEETPLCCPUEtherCAT/CANopen

3C



IO

- IO240
- 122

ARM+FPGA

- ARM+FPGA
- 8200K4100KABCCW+CW/
-

EtherCAT

- 500μs,16
- 1*EtherCAT+2*EtherNet32

MODBUS CAN EtherNet/IP USB CANopen MODBUS-TCP

- MODBUSCANCANopen
- EtherNet/IPUSBMODBUS-TCP
- 5Socket20USB

AC

	x x				
MU300-0808BTA16	8	DC24V	8	-16	4
MU300-0808BTA8	8	DC24V	8	-8	4
MU300-1210BTA16	12	DC24V	10	-16	4
MU300-1210BTA8	12	DC24V	10	-8	4
MU300-1210BRA16	12	DC24V	10	-16	
MU300-1210BRA8	12	DC24V	10	-8	
MU300-2424BTA16	24	DC24V	24	-16	8
MU300-2424BTA8	24	DC24V	24	-8	8

MU200

MU200 Series Small PLC

MU200PLCARM+FPGAR232/RS485/

12200K

8

3C



MODBUS CANopen

- MODBUSCAN
- USB, MODBUS-TCP, 5
- Socket20

ARM+FPGA

- ARM+FPGA
- 12200K8
-

IO

- IO272
- 122

ARM+FPGA

-
-
- C
-
-

AC

	x x		
MU200-4040BTA	40	DC24V	40
MU200-4040BRA	40	DC24V	40
MU200-3232BTA	32	DC24V	32
MU200-3232BRA	32	DC24V	32
MU200-2424BTA	24	DC24V	24
MU200-2424BRA	24	DC24V	24
MU200-1616BTA	16	DC24V	16
MU200-1616BRA	16	DC24V	16

IO MU300/MU200

	x x		
MU200-0016ERN	16	60mm x 90mm x 85mm	
MU200-0016ETN	16		
MU200-1600ENN	16 DC24V		
MU200-0808ERN	8 DC24V 8		
MU200-0808ETN	8 DC24V 8		

MU300/MU200

	x x		
MU200-4AD	4	60mm x 90mm x 85mm	
MU200-4DA	4		
MU200-8AD	8		
MU200-8TC	8		
MU200-4PT	4		

MU300/MU200

	x x		
MUE-4X	4 IO	38mm x 46.4mm x 11.5mm	
MUE-4Y	4 IO		
MUE-4XY	2 2 IO		
MUE-2AD	2		
MUE-2DA	2		
MUE-2AM	1		
MUE-RS232	RS232		
MUE-RS485	RS485		
MUE-CAN	CAN		

MC700 MC700 Series Motion Controller

MC700 EtherCat C




- EtherCat
- 6 2M 2 2M
- 6 200K 6 200K
- CAD



- 2 RS485 1 RS232 SD



- 320K C 2M Byte 2M Byte



		MC700P6	MC700E
	x x	260mm x 140mm x 27mm	
	Ethernet	24V	
	RS485	2	
	RS232	1	
10	200KHz	6 2M	4 200KHz
IO		6	6
		26	24
		22	26
	6	2	EtherCAT
		EIA/TIA-485	-
		2MHz	-
	AB / +	-	-
EtherCAT		COE	IO 250us
	C	320K	
	SD	2M byte	
		2M byte	
	C	2ms/100K	
		2400dmips	
		32	
	G		
	CAD		
C	C		
		C	C

MC280/MC200E

MC280/MC200E Series Motion PLC

MC280/ MC200E

MEGMEET

ARM+FPGA

0.065μs



- 32K
- R 32K D 4

-
- 8 200kHz
-
-
- AB
- S
-
-
-

- 8 100kHz
- 4 AB 100kHz 4
- 5V

-
-
-
-
- 4 1024
- G CAD
-
-
-

MC280

					x x	
MC280-1616BTA4	16	24VDC	16	4	170mm x 90mm x 82mm	
MC280-1616BTA6	16	24VDC	16	6		
MC280-1616BTA8	16	24VDC	16	8		
MC280-1616BTA8-C	16	24VDC	16	8		
MC280-3624BTD4A	36	24VDC	24	4	275mm x 90mm x 82mm	
				4		
				2		
MC280-3624BTD6A	36	24VDC	24	6		
				4		
				2		
MC280-3624BTD8A	36	24VDC	24	8		
				4		
MC280-4040BTA4	40	24VDC	40	4		
MC280-4040BTA6	40	24VDC	40	6		
MC280-4040BTA8	40	24VDC	40	8		

MC200E

					x x	
MC200E-1616BTA4	16	24VDC	16	4	170mm x 90mm x 82mm	
MC200E-1616BTA6	16	24VDC	16	6		
MC200E-1616BTA8	16	24VDC	16	8		
MC200E-3624BTD4A	36	24VDC	24	4	275mm x 90mm x 82mm	
				4		
				2		
MC200E-3624BTD6A	36	24VDC	24	6		
				4		
				2		
MC200E-3624BTD8A	36	24VDC	24	8		
				4		
MC200E-4040BTA4	40	24VDC	40	4		
MC200E-4040BTA6	40	24VDC	40	6		
MC200E-4040BTA8	40	24VDC	40	8		

	G							I		
				3	4		I			
MC280-1616BTA4										
MC280-1616BTA6		1	1	1	1	1	1	100KHZ	-	1
MC280-1616BTA8										
MC280-1616BTA8-C	-	-	-	-	-	-	-	-	2	1
MC280-3624BTD4A										
MC280-3624BTD6A		2	2	2	2	2	2	100KHZ	4	8
MC280-3624BTD8A										
MC280-4040BTA4										
MC280-4040BTA6		2	2	2	2	2	2	100KHZ	4	8
MC280-4040BTA8										
MC200E-1616BTA4										
MC200E-1616BTA6	-	-	-	-	-	-	-	-	-	1
MC200E-1616BTA8										
MC200E-3624BTD4A										
MC200E-3624BTD6A	-	-	-	-	-	-	-	-	-	1
MC200E-3624BTD8A										
MC200E-4040BTA4										
MC200E-4040BTA6	-	-	-	-	-	-	-	-	-	1
MC200E-4040BTA8										

MC200

MC200 Series Small PLC

MC200

,



- 12K
- 0.09μs

- 85V~280V
-
-

- 8

AC

				x	x
MC200-2012BRA	20	24VDC	12	158mm x 90mm x 82mm	
MC200-2012BTA	20	24VDC	12		
MC200-3232BRA	32	24VDC	32	228mm x 90mm x 82mm	
MC200-3232BTA	32	24VDC	32		
MC200-4040BRA	40	24VDC	40	275mm x 90mm x 82mm	
MC200-4040BTA	40	24VDC	40		

- IO 512
- 8
- IO

- MCBUS MODBUS OPC
- CAN CANopen
- Ethernet MODBUS TCP/IP

IO

MC280/MC200E/MC200

				x	x
MC200-0800ENN	8	24VDC		58mm x 90mm x 82mm	
MC200-1600ENN	16	24VDC			
MC200-0008ERN	8				
MC200-0008ETN	8				
MC200-0808ERN	8	24VDC	8		
MC200-0808ETN	8	24VDC	8		
MC200-0016ERN	16			158mm x 90mm x 82mm	
MC200-0016ETN	16				
MC200-1616ERN	16	24VDC	16		
MC200-1616ETN	16	24VDC	16		
MC200-1616ERA	16	24VDC	16		
MC200-1616ETA	16	24VDC	16		

MC280/MC200E/MC200

				x	x
MC200-2AD MC200-4AD	2	4		58mm x 90mm x 82mm	
MC200-2DA MC200-4DA	2	4			
MC200-8AD	8				
MC200-4AM	2		2		
MC200-5AM	4		1		
MC200-2TC MC200-4TC	2	4			
MC200-8TC	8				
MC200-2PT MC200-4PT	2	4			
MC200-2HC	2		200K 100K 1 20K		

MC280/MC200E/MC200

		x	x
MC200-CPM	CANopen	58mm x 90mm x 82mm	
MC200-CAN	CAN		
MC200-RS485	RS485		
MC200-WEN			

MC100

MC100 Series Micro PLC

MC100

PLC

16~60



16K

0.3μs

4

6

50KHz

2

100KHz

8

MCBUS


MODBUS

OPC

		mm	×	×		
AC						
MC100-1006BRA	10	24VDC	6	135 × 90 × 79.2		
MC100-1006BTA	10	24VDC	6			
MC100-1410BRA	14	24VDC	10			
MC100-1410BTA	14	24VDC	10			
MC100-1614BRA	16	24VDC	14	150 × 90 × 79.2		
MC100-1614BTA	16	24VDC	14			
MC100-1614BRA1	16	24VDC	14	2	1	182 × 90 × 79.2
MC100-1614BTA1	16	24VDC	14	2	1	
MC100-2416BRA	24	24VDC	16			
MC100-2416BTA	24	24VDC	16			
MC100-3624BRA	36	24VDC	24	224.5 × 90 × 79.2		
MC100-3624BTA	36	24VDC	24			
DC						
MC100-1006BRD	10	24VDC	6	135 × 90 × 79.2		
MC100-1006BTD	10	24VDC	6			
MC100-1410BRD	14	24VDC	10			
MC100-1410BTD	14	24VDC	10			
MC100-1614BRD	16	24VDC	14	150 × 90 × 79.2		
MC100-1614BTD	16	24VDC	14			
MC100-2416BRD	24	24VDC	16	182 × 90 × 79.2		
MC100-2416BTD	24	24VDC	16			
MC100-3624BRD	36	24VDC	24	224.5 × 90 × 79.2		
MC100-3624BTD	36	24VDC	24			

		mm × ×		
IO				
MC100-0800ENN	8 24VDC			61 × 90 × 73.1
MC100-1600ENN	16 24VDC			
MC100-0008ERN	8			
MC100-0008ETN	8			
MC100-0016ERN	16			
MC100-0016ETN	16			
MC100-0808ERN	8 24VDC	8		
MC100-0808ETN	8 24VDC	8		
MC100-2AD				61 × 90 × 73.1
MC100-2DA	2			
MC100-4AD	4			
MC100-4DA	4			
MC100-5AM	4	1		
MC100-2TC	2			
MC100-4TC	4			
MC100-2PT	2			
MC100-4PT	4			
MC100-1WT	1			
MC100-2WT	2			

PLC		
MCA200-CA10	PLC USB 2m	USB-MiniDin8
MCA200-CA01	PLC RS232 2m	DB9F-MiniDin8
MCA200-CA02	PLC RS232 2m	DB9F-MiniDin8
MCA200-CA17	PLC RS485 2m MC280	USB-MiniDin8
MCA200-CA18	PLC RS485 2m	MiniDin8-RS485
MCA200-CA11	USB RS232 2m	USB-DB9M
MCA200-CA04	MC200 0.65m	() ()
MCA200-CA05	MC200 2m	() ()
MCA200-CA09	MZ600 PLC RS232 3.5m	DB9M-MiniDin8
MCA200-CA14	MZ600 PLC RS232 2m	DB9M-MiniDin8
MCA200-CA16	MZ800 PLC RS232 8m	DB9M-MiniDin8
MCA200-CA01	MZ800 PLC RS232 2m	DB9M-MiniDin8
MCA200-CA12	MC120/MC160/ 2m	USB-RS485
MCA200-CA13	/ 2m	USB-RJ45
MCA200-UDM01SL1	MCA200-UDM01 PLC	RJ45-MiniDin8



MC5000S

I/O

MC5000S Series Remote I/O Module

MC5000S

I/O

MEGMEET

I/O

-
-
-
-
- 12
-
-
-
-



1~12 MC5000

	MC5000S-ET	MC5000S-EIP	MC5000S-PN
	24VDC -15% ~ +20%		
x x	100mm x 34mm x 113mm	102mm x 52.2mm x 110.5mm	102mm x 52.2mm x 110.5mm
IO	12		
	0.5ms		
	EtherCAT Slave	Ethernet/IP Slave	Profinet Slave
	100Mbps		
	100M		
	1ms		
	● MC5000 MC6000 PLC ● Beckho Siemens PLC ● Mitsubishi KEYENCE Omron PLC ● Codesys PLC		

MDT

MDT Series Temperature Controller

MDT

LED

500VDC

50Hz/60Hz

2

2

-
- MtcCompanion /
-
-

	24VDC -15% ~ 20%			
		K J E N T R B		
		Pt100 JPt100 Cu100 Ni120		
		0.2%	+	0.3%
		25ms/	100ms/8	100ms/4
		SSR		
		ON/OFF	PID	PID PID
		14		
		1/2		
	0.1s - 10s		1s - 100s	
	1/2			
	1	RS485	:	MODBUS MCBUS
	10~90%RH			
	2000m			
	IP20			
	IEC/EN 61326-1 For use in industrial locations CE			

MDT-01R-R	1			
MDT-01R-T	1			
MDT-01T-R	1			
MDT-01T-T	1			
MDT-02R-R	2			
MDT-02R-T	2			
MDT-02T-R	2			
MDT-02T-T	2			

MTC/MTCW/MTCV


MTC/MTCW/MTCV Series Temperature Controller

MTC/MTCW/MTCV

(11216)

PID

MtcCompanion / PID1412PLCHMI



	24VDC -15% ~ 20%									
		K J E N T R B								
		Pt100 JPt100 Cu100 Ni120								
		0.2%	+	0.3%						
		25ms/		100ms/8		100ms/4				
		SSR								
		ON/OFF	PID	PID		PID				
		14								
		8								
IO										
		4								
	0.1s - 10s			1s - 100s						
	4		8							
	MTCV									
	MTC/MTCV	RS485	MODBUS		MCBUS					
	MTCW	RS485	RS485		MODBUS					
		-20~60			-40~70					
		10~90%RH			5~95%RH					
		2000m								
		IP20								
	IEC/EN 61326-1 For use in industrial locations UL61010-1 CE UL									

MTC

MTC-04-NT	4	(4)		
MTC-08-NT	8	(8)		
MTC-04-NTT	4	(4)	(8)	
MTC-04-NTR	4	(4) (8)	(8)	
MTC-04-NVT	4	(4) (8 0-20mA 4-20mA) (8 0-1V 0-5V 0-10V 1-5V)	(4)	

MTCW2 RS485

MTCW-04-NTT	4	(4)	(4)	
MTCW-04-NI	4	(4 0-20mA 4-20mA)		
MTCW-04-NV	4	(4 0-1V 0-5V 0-10V 1-5V)		
MTCW-08-NN	8			
MTCW-08-NI	8	(8 0-20mA 4-20mA)		
MTCW-08-NV	8	(8 0-1V 0-5V 0-10V 1-5V)		
MTCW-08-NTT	8	(8)	(8)	
MTCW-12-NT	12	(12)		
MTCW-16-NN	16			
MTCW-08-CT	8	(8)		(8)
MTCW-08-NTD	8	(8) (8)		

MTCV1 RS485

MTCV-16-NT	16	(16)		
MTCV-08-NT	8	(8)		

MTCE EtherCat

EtherCat

± 0.15

± 0.2

0.1


1ms

PID



	24VDC -15% ~ 20%				
		K J E N T R B			
		Pt100 JPt100 Cu100 Ni120			
		0.15% +			
		0.3%			
		25ms/	100ms/8	100ms/4	
		SSR			
		10			
		ON/OFF	PID	PID	PID
		14			
		SSR			
		10			
	0.1s - 10s		1s - 100s		
	10				
	EtherCAT				
		-20~60		-40~70	
		10~90%RH		5~95%RH	
		2000m			
		IP20			
	IEC/EN 61326-1 For use in industrial locations CE				

MTCE-10T-NT	10			
MTCE-10R-NT	10			



	24VDC -15% ~ 20%			
		K J E N T R B		
		Pt100 JPt100 Cu100 Ni120		
		0.15%	+	0.3%
		25ms/	100ms/8	100ms/4
		SSR		
		4/8		
		ON/OFF	PID	PID PID
		14		
		SSR		
		4/8		
	0.1s - 10s 1s - 100s			
	6/8			
	10~90%RH × Ö Ş			

0. Ş

MCAS-06-NI	6	(6 0-20mA 4-20mA)			
MCAS-06-NV	6	(6 0-1V 0-5V 0-10V 1-5V)	SSR	6	Æ
MCAS-08-NI	8	(6 0-20mA 4-20mA)			
MCAS-08-NV	8	(8 0-1V 0-5V 0-10V 1-5V)			
MCAS-08-NTT	8	(8)	(8)		

MQT

MQT Series Temperature Controller

MQT

PID




± 0.15

0.1 PID

PID

PUSH IN

CT



	24VDC -15% ~ 20%				
		K J E N T R B			
		Pt100 JPt100 Cu100 Ni120			
		0.15%		+	
		0.3%			
			25ms/	100ms/8	100ms/4
		SSR			
		ON/OFF	PID	PID	PID
		14			
		8			
		4			
	0.1s - 10s		1s - 100s		
	4		8		
	RS485/Modbus-TCP/EtherNet/EtherCAT/Profinet				
		-20~60		-40~70	
		10~90%RH		5~95%RH	
		2000m			
		IP20			
	IEC/EN 61326-1 For use in industrial locations CE				

MQT				
MQT-2TT-ME	2	Modbus TCP/IP/Ethernet	(4)	
MQT-2RT-ME	2	Modbus TCP/IP/Ethernet	(4)	
MQT-2TT-ET	2	EtherCAT	(4)	
MQT-2RT-ET	2	EtherCAT	(4)	
MQT-2TT-RS	2	Modbus RS485	(4)	
MQT-2RT-RS	2	Modbus RS485	(4)	
MQT-2TT-PN	2	Profinet	(4)	
MQT-2RT-PN	2	Profinet	(4)	
MQT				
MQT-4TT	4	Modbus RS485	(4)	
MQT-4TA	4	Modbus RS485	(4)	
MQT-4TR	4	Modbus RS485	(4)	
MQT-4RT	4	Modbus RS485	(4)	
MQT-4RA	4	Modbus RS485	(4)	
MQT-4RR	4	Modbus RS485	(4)	
MQT				
MQT-8DI	8	8	-	(8)
MQT-8DO	8	8	(8)	-
MQT-8CT	8	8	-	
MQT-8DM	8	4 4	(4)	(4)
MQT-8AI	8	8	-	(8)
MQT-8AV	8	8	-	(8)
MQT-8AO	8	8	(8)	-

MZ800



MZ800 Series Human-Machine Interface


MZ800

PLC

G

PLC

					
	MZ800-TT05SK30/31	MZ800-TT107SK30	MZ800-TT207SK30/31	MZ800-TT207SK30/31W	MZ800-TT210SK30/31
	4.3 16:9 TFT LCD	7 16:9 TFT LCD	7 16:9 TFT LCD	7 16:9 TFT LCD	10.1 16:9 TFT LCD
	480 x 272	800 x 480	1024 x 600		
	TFT (LCD)				
T/B/L/R	50 70 70 70	50 70 70 70	30:50 70 70 70 30:85 85 85 85	85 85 85 85	85 85 85 85
	30:360/31:300	250	30:360/31:450	350	400
	24	16	24		
	4				
	600MHz ARM Cortex-A8	720MHz ARM	1.2GHz ARM Cortex-A7		
	128MB Flash+ 128MB DDR3	64MB RAM+ 128MB Flash	128MB DDR3+4GB EMMC		
RTC					
	30: 31:10M/100M		30: 31:1 10M/100M		
SD			30: 31:		
USB	1 USB Slave 2.0 1 USB Host 2.0				
	COM1: RS232/RS485/RS422 COM3: RS232			COM1: RS232/RS485/RS422 COM2: RS485/RS422 COM3: RS232	
	5W	10W			
	DC24V		DC 9V~28V		
	5ms				
CE	EN61000-6-2:2005	EN61000-6-4:2007	RoHS	± 1KV ± 2KV	4KV 8KV
	30:-20~50 /31:-25~75	0~50			
	30:-25~60 /31:-30~80	-20~60			
	10~90%RH ()				
	10~25Hz (X Y Z 2G/30)				
	IP65 ()		IP20		
	30: 31: +				
	30:130 x 104 x 32 31:130 x 104 x43	204 x 145 x 33.8			273 x 213 x 36
	120 x 93	192 x 138			260 x 202

					
	MZ800-TT210SK30W	MZ800-TT215SK31	MZ800-TT07SK31M	MZ800-TT210SK31M	MZ800-TT22P
	10.1 16:9 TFT LCD	15.6 16:9 TFT LCD	7 16:9 TFT LCD	10.1 16:9 TFT LCD	22 16:9 TFT LCD
	1024 x 600	1920x 1080	800 x 480	1024 x 600	1920x 1080
	TFT (LCD)				
T/B/L/R	85 85 85 85	85 85 85 85	50 70 70 70	85 85 85 85	85 85 80 80
	400	250	360	400	250
	24	16	24		16
	4				Glass+Glass
	1.2GHz ARM Cortex-A7	1G ARM Cortex-A8	600MHz ARM Cortex-A8		800MHz ARM Cortex-A8
	128MB DDR3+4GB EMMC	256MB Flash+512MB DDR3	128M Flash+128M DDR3		256MB Flash+256MB DDR3
RTC					
	30: 31:1 10M/100M	2 10M/100M	10M/100M		1 10M/100M
SD					
USB	1 USB Slave 2.0 1 USB Host 2.0				
	COM1: RS232/RS485/RS422 COM2: RS485/RS422 COM3:RS232	COM3: RS232/RS485/RS422 COM2: RS485	COM1/COM2: RS232/RS485/RS422 COM3/COM4: RS232	COM1: RS232/RS485/RS422 COM2: RS485/RS422 COM3:RS232	COM1/COM2: RS232/RS485/RS422 COM3/COM4:RS232
	10W	18W	10W		20W
	DC24V DC 9V~28V	DC24V DC 18V~28V			
	5ms				
CE	EN61000-6-2:2005	EN61000-6-4:2007	RoHS ± 1KV ± 2KV	4KV	8KV
	0~50	0~50	-20~70	-10~60	-20~70
	-20~60	-20~60	-30~80	-20~70	-20~60
	10~90%RH ()				
	10~25Hz (X Y Z 2G/30)				
	IP65 ()		IP20		
			+		+
	273 x 213 x 36	394x 256 x 36	200 x 146 x 40	274 x 214 x 39	530 x 338 x 61
	260 x 202	380 x 245	192 x 138	260 x 202	502 x 302